

GENERAL:

1. Suitable for dehydrating and drying after metal spare parts are grinded or dipped in oil, water or anti-rust liquid.
2. A machine necessary for dehydrator for electroplating works and grinding works.



PURPOSE:

1. With step less speed change and low-speed start-up device can avoid products from being damage.
2. Simultaneous dehydration and drying process causes no watermarks and dots appearing on the faces, thus raising the brightness and the quality of the products.
3. It is not only dries quickly but also can reclaim various anti-rust liquids or oil in addition to the advantages.

MODEL	WATT	DIMENSION L x W x H	WEIGHT	VOLUME	MOTOR	BARREL SIZE	BARREL HEIGHT
D-365	0.75kw	900 * 700 * 700	220 KGS	25L*60%	1HP	360mm	250mm
D-400	0.75kw	900 * 700 * 780	250 KGS	40L*60%	1HP	405mm	320mm
D-510	1.5kw	1130 * 1000 * 850	305 KGS	65L*60%	2HP	505mm	350mm
D-605	2.25kw	1130 * 1000 * 870	350 KGS	96L*60%	3HP	600mm	360mm
D-630	3.75kw	1150 * 990 * 900	450 KGS	130L*60%	5HP	630mm	440mm
D-800	3.75kw	1650 * 1200 * 1100	550 KGS	200L*60%	5HP	800mm	400mm

